



<b>Light source</b>	LED
<b>Work equipment</b>	Electronic ballast
<b>Connected load</b>	220 - 240 V; 50 Hz; 60 Hz
<b>Power consumption</b>	ca. 14 W
<b>Standby</b>	ca. 0,2 W
<b>Power factor</b>	env. 0,90
<b>Luminous flux</b>	approx. 1.400 lm
<b>Light type/-color</b>	Warm white
<b>Colour temperatur</b>	approx. 3.000 K
<b>Color rendering index</b>	CRI ≥ 80
<b>Light distribution</b>	Direct
<b>Direct ratio</b>	approx. 100 %
<b>Beam angle</b>	64°
<b>Chromaticity tolerance LED</b>	< 3 SDCM
<b>Glare control</b>	Prism aperture
<b>Luminance (L65)</b>	≤ 2.100 cd/m <sup>2</sup>
<b>Unified glare rating (4H 8H) <sup>1)</sup></b>	≤ 19
<b>System of protection <sup>2)</sup></b>	IP 20; 22
<b>Class of protection</b>	II
<b>Technology</b>	Continuously dimmable
<b>Operation</b>	External
<b>Housing</b>	Sheet metal; White
<b>Mains lead</b>	ca. 0,35 m; Connector
<b>Design</b>	Integrated version
<b>Fastening</b>	Tension spring
<b>EAN</b>	4013330041557
<b>Weight (net)</b>	ca. 0,7 kg
<b>Special features</b>	Flicker-free; Integration into DALI light management systems; As supplement for room depths and walking areas; Suitable as emergency lighting; Ceiling installation without tools by means of tension springs; Low installation depth thanks to external ballast; TouchDIM - dimming via standard switch; Strain relief with the possibility of through-wiring

<sup>1)</sup> according to DIN EN 12464-1:2021  
<sup>2)</sup> Higher degree of protection when installed.