



<b>Work equipment</b>	Electronic ballast dimable digital
<b>Connected load</b>	220 - 240 V; AC; 50 Hz; 60 Hz
<b>Power consumption</b>	ca. 40 W
<b>Luminous flux</b>	approx. 5.600 lm
<b>Luminous efficiency <sup>1)</sup></b>	approx. 140 lm/W
<b>Light type/-color</b>	Warm white
<b>Colour temperatur</b>	approx. 3.000 K
<b>Color rendering index</b>	CRI ≥ 80
<b>Light distribution</b>	Direct/indirect
<b>Direct ratio</b>	approx. 41 %
<b>Chromaticity tolerance LED</b>	< 3 SDCM
<b>Glare control</b>	Diffusor
<b>System of protection</b>	IP 20
<b>Class of protection</b>	I
<b>Technology</b>	Continuously dimmable
<b>Operation</b>	External
<b>Emergency lighting</b>	none
<b>Housing</b>	Sectional aluminium; Anodised; Aluminium coloured anodised
<b>Light source cover</b>	Acrylic (PMMA); White opal
<b>Mains lead</b>	Connector; 5 pin
<b>Design</b>	mounted version
<b>Fastening</b>	Wall bracket
<b>Maximum ambient temperature</b>	25 °C
<b>Life expectancy LED</b>	L80B50 50.000h
<b>EAN</b>	4013330146061
<b>Weight (net)</b>	ca. 3,3 kg
<b>Dimensions</b>	1.050 mm; 142 mm; 29 mm
<b>Special features</b>	DIN EN 60598-2-25; Asymmetric radiation; DALI Load 1x; Integration into DALI light management systems; Suitable as emergency lighting

<sup>1)</sup> For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear