


Wall-mounted luminaire ZERA.bed ZEW 11000/830

114487000-00813009


Waldmann **W**

ENGINEERS OF LIGHT



5 pin

C43 ↓46.9% ↑53.1% Φ: 9800 lm



Work equipment	Power supply unit
Connected load	220 - 240 V; AC; 50 Hz; 60 Hz
Power consumption	ca. 122 W
Luminous flux	approx. 10.890 lm
Luminous efficiency ¹⁾	approx. 89 lm/W
Light type/-color	Warm white
Colour temperatur	approx. 3.000 K
Color rendering index	CRI ≥ 80
Light distribution	Direct/indirect
Chromaticity tolerance LED	< 3 SDCM
Glare control	Diffusor
System of protection	IP 20
Class of protection	I
Technology	Switchable
Operation	Switch
Emergency lighting	none
Housing	Sectional aluminium; Anodised; Aluminium coloured anodised
Light source cover	Acrylic (PMMA); White opal
Mains lead	Connector; 5 pin
Design	mounted version
Fastening	Wall bracket
Maximum ambient temperature	25 °C
Life expectancy LED	L80B50 50.000h
EAN	4013330146269
Weight (net)	ca. 6,9 kg
Dimensions	1.049,5 mm; 228 mm; 29 mm
Special features	General light, indirect, 3000K, Ra≥80; Night light; indirect; 2700K; Ra≥80; Reading light, direct, 2700K, Ra≥90; Examination light, direct, direkt, 4000K, 60W, Ra≥95, R9≥50; Switch right; DIN EN 60598-2-25

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control g