



<b>Work equipment</b>	Power supply unit
<b>Connected load</b>	220 - 240 V; AC; 50 Hz; 60 Hz
<b>Power consumption</b>	ca. 22 W
<b>Luminous flux</b>	approx. 2.100 lm
<b>Luminous efficiency <sup>1)</sup></b>	approx. 95 lm/W
<b>Light type/-color</b>	Warm white
<b>Colour temperatur</b>	approx. 3.000 K
<b>Color rendering index</b>	CRI ≥ 80
<b>Light distribution</b>	Direct
<b>Direct ratio</b>	approx. 84 %
<b>Chromaticity tolerance LED</b>	< 3 SDCM
<b>Glare control</b>	without
<b>Luminance (L65)</b>	≤ 3.500 cd/m <sup>2</sup>
<b>Unified glare rating (4H 8H) <sup>2)</sup></b>	≤ 22
<b>Class of protection</b>	I
<b>Technology</b>	Continuously dimmable; DALI
<b>Operation</b>	External
<b>Housing</b>	Sheet metal; Painted; White
<b>Light source cover</b>	Acrylic (PMMA); White opal
<b>Mains lead</b>	Direct power supply
<b>Design</b>	mounted version
<b>Fastening</b>	Ceiling mounted
<b>EAN</b>	4013330147808
<b>Weight (net)</b>	ca. 1,2 kg
<b>Dimensions</b>	85 mm
<b>Special features</b>	DALI Load 1x

<sup>1)</sup> For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear according to DIN EN 12464-1:2021

<sup>2)</sup>