



A40 ↓ 100.0% Φ: 1450 lm




100 x 100 cm Φ: 1450 lm

Em: 852 lx
E_{max}: 1890 lx
E_{min}: 276 lx
= 50 cm



Φ: 1450 lm E 0°



Light source

Work equipment

Connected load

Power consumption

Luminous flux

Luminous efficiency ¹⁾

Light type/-color

Colour temperatur

Color rendering index

Light distribution

Beam angle

Chromaticity tolerance LED

Glare control

Luminance (L65)

UGR class (4H 8H; EN 12464-1)

System of protection/Class

Technology

Operation

Housing

Light source cover

Arm

Balance of articulation joints

Mains lead

Fastening

EAN

Weight without/incl. packaging

Special features

LED

Without

22 - 26 V; DC

ca. 16 W

approx. 1.450 lm

approx. 90 lm/W

Cold white

approx. 5.000 K

CRI ≥ 80

Direct; approx. 100 %

110°

< 4 SDCM

Diffusor

≤ 23.000 cd/m²

≤ 28

IP 65; III

Switchable; Continuously dimmable

Push button

Aluminium; Painted; Jet black

Polycarbonate (PC); White opal

Tubular aluminium section; Anodized; Black

Spring

ca. 3 m; With free stranded wires

Table clamp (accessory); Wall bracket (accessory);

Screw-down flange

4013330193218

ca. 1,7 kg

Fully spring-relieved arm

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear

