


CEE 7/VII

D53 | 15.0% | 85.0% Φ : 11650 lm
UGR 4H 8H: <10 / <10



Light source

Work equipment

Connected load

Power consumption

Power factor

Luminous flux

Luminous efficiency ¹⁾

Light type/-color

Colour temperatur

Color rendering index

Light distribution

Direct ratio

Chromaticity tolerance LED

Glare control

Luminance (L65)

Unified glare rating (4H 8H) ²⁾

System of protection

Class of protection

Technology

Operation

Emergency lighting

Housing

Light source cover

Luminaire base

Mains lead

Fastening

Decorative contrast side parts

Life expectancy LED

EAN

Weight (net)

Dimensions

Special features

LED

Electronic ballast

220 - 240 V; AC; 50 Hz; 60 Hz

ca. 77 W

env. 0,93

approx. 11.650 lm

approx. 151 lm/W

Cold white

approx. 4.000 K

CRI \geq 80

Direct/indirect; Steel tube; Painted; Tubular section upright; White approx. 15 %

< 3 SDCM

Prism aperture

\leq 3.000 cd/m²

\leq 16

IP 20

I

Presence and daylight sensor control (PIR); DALI

Multi-function switch

none

Steel/plastic; Painted; White

Acrylic (PMMA); Satine

C-form flat

ca. 3 m; Mains plug; CEE 7/VII

Floor standing base

Flint grey

L80B50 60.000h

4013330103392

ca. 19,7 kg

2.035 mm

Integrated light and presence sensor PIR; Separated, direct and indirect light individually adjustable; Retrofittable with TALK module; Flicker-free; Cradle to Cradle Certified TM; Direct light component with edge light and light-guide technology for homogenous light exit; Luminaire head detachable

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear according to DIN EN 12464-1:2021

²⁾