



Work equipment

Connected load

Power consumption

Luminous flux

Luminous efficiency ¹⁾

Light type/-color

Colour temperatur

Color rendering index

Light distribution

Direct ratio

Chromaticity tolerance LED

Glare control

Luminance (L65)

Unified glare rating (4H 8H) ²⁾

System of protection

Class of protection

Technology

Operation

Emergency lighting

Housing

Light source cover

Mains lead

Fastening

EAN

Weight (net)

Dimensions

Special features

Electronic ballast

220 - 240 V; AC; 50 Hz; 60 Hz

ca. 79 W

approx. 7.200 lm

approx. 91 lm/W

dynamic white; Warm white; Daylight

approx. 2.700 - 6.500 K

CRI \geq 90

Direct/indirect; Wood; Stained; Tubular section upright; Ash dark approx. 44 %

< 3 SDCM

Diffusor

\leq 1.600 cd/m²

\leq 16

IP 20

I

Continuously dimmable; DALI

Pull cord

none

Polyethylene(PE); Untreated; Anthracite

Polycarbonate (PC); Satine

ca. 3,4 m; Mains plug; CEE 7/VII

Floor standing base

4013330147679

ca. 6,4 kg

1.660 mm

App control; Biodynamic light VTL

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear according to DIN EN 12464-1:2021

²⁾