



Work equipment	Electronic ballast dimable digital
Connected load	220 - 240 V; AC; 50 Hz; 60 Hz
Power consumption	ca. 18 W
Luminous flux	approx. 2.800 lm
Luminous efficiency ¹⁾	approx. 155 lm/W
Light type/-color	Warm white
Colour temperatur	approx. 3.000 K
Color rendering index	CRI ≥ 80
Light distribution	Direct/indirect
Direct ratio	approx. 41 %
Chromaticity tolerance LED	< 3 SDCM
Glare control	Diffusor
System of protection	IP 20
Class of protection	I
Technology	Continuously dimmable
Operation	External
Emergency lighting	none
Housing	Sectional aluminium; Anodised; Aluminium coloured anodised
Light source cover	Acrylic (PMMA); White opal
Mains lead	Connector; 5 pin
Design	mounted version
Fastening	Wall bracket
Maximum ambient temperature	25 °C
Life expectancy LED	L80B50 50.000h
EAN	4013330146108
Weight (net)	ca. 6,9 kg
Dimensions	550 mm; 142 mm; 29 mm
Special features	DIN EN 60598-2-25; Asymmetric radiation; DALI Load 1x; Suitable as emergency lighting

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear