






Free-standing luminaire LAVIGO.single DPS 15000/940/R/WS/CEE/0N/C/G3

121865000-00816448



Work equipment

Connected load

Power consumption

Luminous flux

Luminous efficiency¹⁾

Light type/color

Colour temperatur

Color rendering index

Light distribution

Chromaticity tolerance LED

Glare control

Luminance (L65)

UGR class (4H 8H; EN 12464-1)

System of protection/Class

Technology

Operation

Housing

Light source cover

Arm

Luminaire base

Mains lead

Fastening

Decorative contrast side parts

Life expectancy LED

Energy efficiency class

EPREL number of lightsources

EAN

Weight without/incl. packaging

Special features

Electronic ballast

220 - 240 V; AC; 50 Hz; 60 Hz

ca. 90 W

approx. 15.000 lm

approx. 166 lm/W

Cold white

approx. 4.000 K

CRI ≥ 90; R9 ≥ 50

Direct/indirect

< 3 SDCM

Prism aperture

≤ 3.000 cd/m²

≤ 16

IP 20; I

Presence and daylight sensor control (PIR)

Multi-function switch

Steel/plastic; Powder coatet; White

Acrylic (PMMA); Structured

Steel tube; Powder-coated; Tubular section upright; White
C-form

ca. 3 m; Mains plug; CEE 7/VII

Floor standing base

Jet black

L80B50 60.000h

B; C

2226196; 2226239

4013330191030

ca. 18,3 kg

Integrated light and presence sensor PIR;
Asymmetric radiation; Separated, direct and indirect light individually adjustable; Flicker-free;
Cradle to Cradle Certified TM; Direct light component with edge light and light-guide technology for homogenous light exit

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control g