





Free-standing luminaire STRAIGHT.single STS 12000/930/R

121888000-00818475



CEE 7/VII



Work equipment

Connected load

Power consumption

Luminous flux

Luminous efficiency¹⁾

Light type/color

Colour temperatur

Color rendering index

Light distribution

Chromaticity tolerance LED

Glare control

Luminance (L65)

UGR class (4H 8H; EN 12464-1)

System of protection/Class

Technology

Operation

Housing

Light source cover

Arm

Luminaire base

Mains lead

Fastening

Decorative contrast side parts

Life expectancy LED

EPREL number of lightsources

EAN

Weight without/incl. packaging

Packaging dimensions

Special features

Electronic ballast

220 - 240 V; AC; 50 Hz; 60 Hz

approx. 106 W

approx. 12.000 lm

approx. 113 lm/W

Warm white

approx. 3.000 K

CRI ≥ 90; R9 ≥ 50

Direct/indirect; approx. 40 %

< 3 SDCM

Optics

≤ 3.000 cd/m²

≤ 16

IP 20; I

Presence and daylight sensor control (PIR)

Multi-function switch

Aluminium/plastic; Powder coatet; White

Acrylic (PMMA); Clear

Tubular aluminium section; Powder-coated;

Tubular section upright; White

T-shaped; White

approx. 3 m; Mains plug; CEE 7/VII

Floor standing base

White

L80B50 60.000h

2226230, 2716887

4013330204426

11,3; approx. 0 kg

approx. 0 mm; 0 mm; 0 mm

Integrated light and presence sensor PIR;
Separated, direct and indirect light individually
adjustable; Flicker-free

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control g